


Bovone ELB 14 – Tooling Setup



	ES: ELB 14 AL: Clear Glass and Mirror	PROCESS: SETS:	Flat Standard and Premium	REM	ARKS:	Standard and Premiu General Application	ım Tools for
POS		DESCRIPTIO	N		STA	ANDARD PART #	PREMIUM PART #
1	Diamond Cup Wheel – Metal (150x45x22ah 100/120 grit	segmented)				DCT1FSA	DCT1SC
2	Diamond Cup Wheel – Metal 150x45x22ah 170/200 grit					DCT2FA DCT2FSA	DCT2SC
3	Diamond Cup Wheel – Resin 150x45x22ah 200 grit		Š	375		DCT3FA	DCT23LFC
4	Diamond Cup Wheel – Resin 150x45x22ah 400 grit		S.			DCT4FA	DCT24LFC
5	Diamond Cup Wheel – Arris (c 130x22ah 325 grit	ontinuous)				ELB14-AD	ELB14-ADC
6	Diamond Cup Wheel – Arris (c 130x22ah 325 grit	ontinuous)				ELB14-AD	ELB14-ADC
7	Diamond Cup Wheel – Resin 150x45x22ah 400 grit		S. Contraction of the contractio			DCT4FA	DCT24LFC
8	Diamond Cup Wheel – Resin (150x45x22ah 600 grit	slotted)	S. Contraction of the contractio			DCT5FLA	DCT25LFC
9	Diamond Cup Wheel – Resin A 130x45x22ah 600 grit	arris (slotted)				ELB14-ART*	DCT20AFC

Additional options available. Contact Salem for more information.

Wheels pictured are from our premium tooling line.

Tooling setup continued on next page.

GO BEYOND THE EDGE


Office: 724.212.3749

^{*}Wheel pictured in positions 9 and 10.

^{**}Axion glass polish is recommended for use with felt wheels on Bovone machines.



Bovone ELB 14– Tooling Setup (Continued)



	ES: ELB 14 AL: Clear Glass and Mirror	PROCESS: SETS:	Flat Standard and Premium	REMAI	RKS: Standard and Pre General Applicati	
POS		DESCRIPTIO	N		STANDARD PART #	PREMIUM PART #
10	Diamond Cup Wheel – Resin A 130x45x22ah 600 grit	Arris (slotted)			ELB14-ART*	DCT20AFC
11	Polishing Wheel – Arris NOVAFelt Felt or Vero Cerium	ı		9	FN5**	FC3050
12	Polishing Wheel – Arris NOVAFelt Felt or Vero Cerium	ı)	FN5**	FC3050
13	Polishing Wheel NOVAFelt Felt or Vero Cerium	ı		•	FN6** FN6P** (ready-mount)	FC5104
14	Polishing Wheel NOVAFelt Felt or Vero Cerium	ı		•	FN6** FN6P** (ready-mount)	FC5104

Additional options available. Contact Salem for more information.

Wheels pictured are from our premium tooling line.

GO BEYOND THE EDGE

Office: 724.212.3749

^{*}Wheel pictured in positions 9 and 10.

^{**}Axion glass polish is recommended for use with felt wheels on Bovone machines.